Heat Transfer Asian Research
Subject Index to Volume 35, 2006

Aerospace propulsion system: **6**, 410-420
Air flow: **1**, 13-19
Apparent viscosity: **7**, 553-567
Arranged in rows: **5**, 351-358
Atomization: **5**, 369-385

Biomass: **7**, 527-538
Boiling: **1**, 35-46
Boiling curve: **1**, 20-34
Boiling two-phase flow: **1**, 47-60
Bubble: **5**, 369-385
Bubble growth: **2**, 165-177

Channel flow: **4**, 265-278
Chimney effect: **2**, 122-136
Combustion: **1**, 75-88
Conjugate heat transfer: **3**, 209-223
Conservative heat transfer: **6**, 410-420
Constant-stress accelerated life test: **2**, 110-114
Contact angle: **7**, 513-526
Cooling blades: **6**, 410-420
Cooling rate: **2**, 115-121
Cooling temperature fluctuation: **4**, 294-308
Corrugated thin plate: **3**, 209-223
CPC (compound parabolic concentrator): **5**, 323-335
Critical heat flux: **1**, 47-60
Critical heat flux (CHF): **7**, 582-588

Damping oscillator model: **2**, 101-109
Delayed neutron precursor: **6**, 434-450
Density: **2**, 152-164
Deployable radiator: **7**, 464-481
DNS: **4**, 265-278
Double-walled carbon nanotubes: **4**, 254-264
Dream pipe: **1**, 61-74
Droplet: **1**, 13-19
Droplet evaporation: **7**, 513-526
Duct blockage accident: **6**, 434-450
Dynamic contact angle: **1**, 1-12

Effect of the thermal boundary condition: **4**, 265-278
Effective thermal conductivity of mixture: **4**, 245-253
Electronic equipment: **2**, 122-136
Energy conversion: **3**, 224-244
Equivalent specific heat method: **2**, 115-121

Film boiling: **1**, 20-34
Fin height: **3**, 179-193, 194-208
Fire: **6**, 387-401
Flame: **7**, 501-512
Flash-boiling: **5**, 369-385
Flow drag reduction effect: **7**, 553-567
Flow measurements: **7**, 501-512
Fouling accelerated life test model: **2**, 110-114
Fouling life: **2**, 110-114
Fouling thermal resistance: **2**, 110-114
Fuel cell: **2**, 89-100, 137-151; **7**, 568-581
Fuel design: **5**, 369-385
Fuel salt flow: **6**, 434-450

Gas turbines: **6**, 410-420
Gasification: **7**, 527-538
Graphite sheet: **7**, 464-481

Heat exchanger: **3**, 179-193, 194-208, 209-223
Heat loss: **7**, 451-463
Heat pipe: **7**, 482-500
Heat-proof glass: **2**, 165-177
Heat radiation: **5**, 336-350
Heat transfer: **1**, 47-60, 61-74; **3**, 194-208, 224-244; **7**, 451-463, 482-500, 582-588
Heat transfer enhancement: **5**, 351-358; **6**, 402-409
Heterogeneous combustion: **4**, 279-293
Hexagonal CPC: **5**, 323-335
High-temperature air combustion: **5**, 359-368

Humidity transport: **2**, 137-151; **7**, 568-581
Hysteresis: **1**, 20-34

Inclination: **2**, 122-136
Infrared spectra: **2**, 101-109
Interference piece: **2**, 165-177
Interference rings: **2**, 165-177
Internal gravity wave: **5**, 309-322
Ionic crystals: **2**, 101-109

KIVA3V: **5**, 369-385

Laser extinction method: **1**, 35-46
Leidenfrost point: **7**, 513-526
Lignin: **7**, 527-538
Liquid nitrogen: **7**, 582-588
Longitudinal vortex: **5**, 351-358; **6**, 402-409
Loop channel: **7**, 482-500
Low Reynolds number: **3**, 209-223

Magnesia particle: **4**, 245-253
Mass transfer: **2**, 137-151; **7**, 568-581
Measurement method: **6**, 421-433
Mechanical ventilation: **6**, 387-401
Micro-channel: **1**, 35-46
Micro-layer thickness: **1**, 35-46
Micro spherical plastic-resin particle: **4**, 279-293
Micro systems: **3**, 224-244
Microlayer: **2**, 165-177
Modeling method: **7**, 451-463
Molecular dynamics method: **4**, 254-264
Molten nitrate: **4**, 245-253
Molten salt reactor: **6**, 434-450
Multicomponent fuel: **5**, 369-385

Narrow channel: **7**, 582-588
Natural air cooling: **2**, 122-136
Natural circulation flux: **2**, 122-136
Natural convection: **2**, 122-136; **4**, 294-308; **5**, 309-322, 351-358
Neutron flux: **6**, 434-450
Non-contact measurements: **2**, 152-164
Non-uniformly heated tube: **1**, 47-60
Nondestructive quality inspection: **6**, 421-433
NO_x emission: **5**, 359-368
Nucleate boiling: **1**, 20-34
Numerical analysis: **4**, 294-308; **5**, 309-322; **7**, 451-463
Numerical investigation: **7**, 539-552
Numerical simulation: **1**, 61-74; **3**, 209-223

Operating parameters: **2**, 89-100
Organic Rankine cycle: **5**, 323-335
Oscillation: **1**, 13-19
Oscillatory flow: **1**, 61-74; **7**, 482-500

Peapods: **4**, 254-264
Phase change: **1**, 35-46
PIV: **7**, 501-512
Polymeric resins: **6**, 421-433
Porosity coefficient of outlet openings: **2**, 122-136
Porous media: **2**, 137-151; **5**, 336-350; **7**, 568-581
Porous medium: **1**, 75-88; **4**, 294-308
Precursor film: **1**, 1-12
Premixed combustion: **7**, 501-512
Pressure difference: **1**, 47-60
Pressure drop: **3**, 179-193
Proton exchange membrane (PEM): **2**, 89-100

Radiant burner: **1**, 75-88
Radiation: **1**, 75-88
Reciprocating flow: **5**, 336-350
Recycled plastic resin: **4**, 279-293
Refrigerator: **7**, 451-463
Regenerator: **5**, 359-368
Resonance: **5**, 309-322
Reversible thermal panel: **7**, 464-481
Rotary actuator: **7**, 464-481
Rotating: **6**, 410-420

Secondary refrigerant: **7**, 553-567
Serrated fin: **3**, 179-193, 194-208
Shape memory alloy: **7**, 464-481
Size effect: **3**, 224-244
Soil solute: **7**, 539-552
Soil water: **7**, 539-552
Solar absorber: **7**, 464-481
Solar collector: **5**, 323-335
Solar energy: **5**, 323-335
Solidification: **4**, 294-308
Solidification latent heat: **2**, 115-121
Spacecraft thermal control: **7**, 464-481
Spherically symmetric one-dimensional analysis: **4**, 279-293
Spiral fin: **3**, 179-193, 194-208
Square cavity: **5**, 309-322
Stationary and abrupt heating: **4**, 279-293
Superadiabatic combustion: **5**, 336-350

Superheated liquid: **2**, 165-177
Surface tension: **2**, 152-164
Surfactant: **7**, 553-567

Tar decomposition: **7**, 527-538
Temperature compensation: **2**, 115-121
Temperature effect: **7**, 539-552
Temperature effectiveness: **3**, 209-223
Thermal conductivity: **6**, 421-433
Thermal decomposition: **7**, 527-538
Thermal design: **2**, 122-136
Thermal electric generation: **5**, 323-335
Thermal energy storage system: **4**, 245-253
Thermal radiation: **2**, 101-109
Thermal recycling: **4**, 279-293
Thermoelectrics: **3**, 224-244
Thermophysical properties: **5**, 336-350
Townhouse building: **6**, 387-401
Transient hot wire method: **4**, 245-253
Transition: **1**, 13-19
Transition boiling: **1**, 20-34
Transport: **7**, 539-552
Tungsten: **2**, 152-164
Turbulent flow: **7**, 501-512
Turbulent heat transfer: **4**, 265-278
Type II-censoring test: **2**, 110-114

Vacuum insulation: **7**, 451-463
Vapor generator: **1**, 35-46
Vaporization: **5**, 369-385
VIP: **7**, 451-463
Viscosity: **2**, 152-164

Water transport: **2**, 89-100
Wetting: **1**, 1-12
Wetting limit temperature: **7**, 513-526

Zone model: **6**, 387-401